

PROFESSIONAL FM/DAB/DAB+ MONITORING RECEIVER

DB7002 is a revolutionary solution that combines in a single, high-precision tool the most important functionalities of two separate types of product. To achieve that, our engineers have equipped this model with two independent tuners - one for FM and one for DAB/DAB+, allowing for the device to perform both FM and DAB/DAB+ monitoring in parallel. It provides detailed and accurate measurement of all of the most important signal parameters and also boasts two loggers with 24 channels apiece for FM and DAB/DAB+. The recorded information is stored in log files on an SD card for easy future analysis and can easily be downloaded via a standard FTP client.

As a product that incorporates DAB/DAB+ monitoring capabilities, DB7002 fully meets the ETSI EN 300 401 DAB standard and offers support for Program Associated Data (PAD), as well as all standard bitrates and VBR, and automatically displays live metadata.

As an FM monitoring tool, DB7002 also provides powerful signal processing capabilities through sophisticated DSP algorithms and offers a Loudness Meter, which allows for measurements to be shown as defined by ITU BS.1770-4 and EBU R128 recommendations.

To make sure the transmission is not interrupted, there are local alarm options and online notifications via rear-panel alarm GPOs, E-mail and SNMP in case there is audio loss or a change in the signal.

DB7002 can also be managed without effort. It is easy to program via the front-panel menu or remotely through your PC, tablet or smart phone via a standard web browser; iOS and Android devices are also supported. The high-resolution OLED graphical display and the ultra-bright LED bar graph indicators allow for easy reading of the main signal parameters. A user-friendly front panel menu in addition to the set of four soft buttons provides easy navigation and quick access to each function.

DB7002 is definitely a must-have. Its two independent tuners set it apart from any other product, while its effectiveness and precision make it the perfect monitoring tool.



FEATURES

- RDS and RBDS decoder with BER meter
- Wide angle, easy to read OLED display
- Levels measurement with data history
- Real Time Audio Program Streaming
- Detailed DAB component information
- Apple and Android devices support
- Restore Factory Parameters option
- Built-in 24 channel FM Data logger
- Very Intuitive Navigational Menu
- DAB/DAB+ compliant receiver
- Built-in WEB and FTP server
- Easy Installation and Setup
- Built-in Loudness Analyzer
- Selectable De-emphasis
- Easy to use WEB interface
- Built-in Stereo Decoder
- High-end digital tuner
- Fully DSP-based core
- Protected access to the device settings
- Selectable wide range IF filter bandwidth
- Built-in 24 channel DAB/DAB+ Data logger
- Professional AES/EBU Digital audio output
- Accurate front-panel metering for local use
- Up to 100 dBμV direct RF Antenna Input
- Wide operating voltage range: 100-240V AC
- Support for Program Associated Data (PAD)
- Headphone output with front panel level control
- FM Band 87.1 - 108 MHz Basic Spectrum Analyzer
- Alarm dispatch via E-mail, SNMP ver.2C and GPO
- Firmware updates will ensure improved operation
- LAN port for full TCP/IP remote control and monitoring
- SNTP for automatic synchronization of the built-in clock
- Bright bar graph LED metering of the RF and Audio Levels
- Adjustable MIN/MAX alarms for RF, Left & Right Audio Levels
- Adjustable, Balanced Analog Audio Outs on XLR Connectors

SPECIFICATIONS

DAB/DAB+ Radio Input

RF frequency range	168 - 240 MHz
DAB/DAB+	Band III Channels 5A - 13F
Sensitivity	18 dBμV
Input connector	BNC 50Ω
In compliance with	ETSI EN 300 401
Ensemble acquisition Time	940 ms
L&R Audio	1%, +5.0 to -50.0 dB, 0.1 dB

DAB/DAB+ Radio Metering

Quality indicators	RSSI, SNR, CNR, FIC Quality, FIB Errors, FFT Offset
PAD	DLS, MOT
Metadata Displayed	Ensemble Label, Component List & ID, Service List & ID, Dynamic Label, PTY, Sample Rate, Bit Rate, Gain, Mode, Service Mode, Protection Info, Current CU & Address, Country, Language, Time & Date

FM Radio Input

Tuning Range	87.1-108 MHz (CCIR)
Tuning Step	10, 20, 50, 100 kHz
Tuner Sensitivity	30 dBμV
Antenna Ports	BNC Connector, 50Ω
Antenna Ports Isolation	> 40 dB
Dynamic range	100 dB

FM Demod

IF Filter Bandwidth	15 Increments (27kHz - 157kHz, Auto)
Dynamic range	90 dB

Size and Weight

Dimensions (W;H;D)	485 x 44 x 180 mm
Shipping Weight	540 x 115 x 300 mm / 2.700 kg

Stereo Decoder

Freq. Response (L&R)	±0.1 dB, 10 Hz to 15 kHz
SNR (Stereo)	60 dB, 50 μs de-emphasis
THD	0.15% @ 1kHz, 0.4% from 10 Hz to 15 kHz, 50 μs de-emphasis
Separation	50 dB, 50 Hz to 10 kHz, 50 μs de-emphasis
Crosstalk	52 dB

RDS Decoder

Standards	European RDS CENELEC; US RBDS NRSC
Error Correction & Counting	Yes
AF Decoding, CT (Time/Date), PI, PTY, DI, MS, TA/TP, RT (Radio Text), PS	
Group Analyzer	Yes
BER Analyzer	Yes
Group Sequence Display	Yes

FM Radio Metering

RF Level	±1 dB, 0 to 100 dBμV
Audio	±1 dB, +10.0 to -55.0 dB, 0.1 dB resolution

Outputs

FM (L&R)	+6 dBm, 600Ω, balanced XLR Connector
DAB/DAB+ (L&R)	+12 dBm, 600Ω, balanced XLR Connector
AES3 (L, R)	5.0 Vp-p, 110Ω, balanced XLR Connector
Alarms	7 Programmable terminals, optoisolated
Headphone	6,3mm (1/4") Phone Jack

Communication Interfaces & Storage

Ethernet 10/100 Base-T	RJ45 Connector
Storage	16GB Build-in Memory Card
Data format	Text, CSV

Power

Voltage	100-240V / 50-60 Hz
Power Consumption	20VA
Connector	IEC320, Fused and EMI-suppressed



WE NEVER SPARE EFFORTS AND RESOURCES TO TURN OUR IDEAS INTO SUCCESSFUL PRODUCTS