

Annuncicom 1000

Professional Intercom / Paging device with supervised contact closures and relay outputs, 48V capable.



The Annuncicom 1000 is a professional Audio over IP device. With balanced audio and supervised I/O, it is ideal to serve as a gateway between IP Paging, VoIP and Intercom systems.

Supporting both high quality music (MP3) as well as voice codecs (G.711 and G.722*) and a large number of protocols (including Shoutcast/Icecast, RTP, SIP etc), the device can be used for both surveillance as well as VoIP applications.

Applications

- VHF Radio Controller and interface to IP
- Microphone Encoder for IP Audio Surveillance
- Automatic Announcement Systems
- Voice Evacuation Systems
- Paging and Audio Distribution with Amplifier control and monitoring
- Live IP Audio Encoder for Streaming Applications
- Generic, bidirectional full-duplex VoIP module for Paging and Intercom applications
- SIP and IP Paging Zone Device

Features

- MP3, G.711, G.722*, PCM Encoding
- MP3, G.711, G.722*, PCM Decoding
- Audio Level Supervision with SNMP Trap generation
- IP Streaming via TCP, UDP, RTP, Multicast
- Microphone Input
- Balanced Line Level Input (2)
- Balanced Line Level Output (2)
- Relay Output (8+1)
- Supervised Contact Closure Input (8)
- RS-232 Serial Port (1)
- RS-485 Serial Port (1)
- Supply Voltage (24-48VDC)
- Battery Backup Supply Input



For commercial related questions (distributors contacts, price list, business opportunities) please contact: sales@barix.com



For technical inquiries (problem reports, request for documentation, etc.) please contact: support@barix.com

Technical Specifications

Audio formats

Format	Encode	Decode
PCM	Y	Y
G.711	Y	Y
G.722*	Y	Y
MP3	VBR, CBR*	VBR, CBR*

Power inputs

- Two independent, level supervised inputs
- 24 to 48 VDC $\pm 20\%$ (pos. or neg.), 8 Watt max.

Discrete Interfaces

- 8 supervised Inputs
- 8 Relays with normally open contacts, max. 50V 1A (dry contacts)
- 1 Fault Relay output

Audio Interfaces

Mic In (Balanced, Phantom power) or Balanced
Balanced Stereo Line In, 18 kOhm impedance

- Input level software controllable
- Clipping level 3.5 dBu, 3.28 Vpp
- Frequency response (-3 dBFS) 20 .. 17000 Hz **
- Signal to Noise Ratio 88 dB, THD (-3 dBFS) < 0.1 %
- Stereo crosstalk -87 dB

Balanced Stereo Line Out, 40 .. 60 Ohm impedance

- Output level software controllable
- Full scale output voltage 5.9 dBu, 4.33 Vpp
- Frequency response (-3 dBFS) 15 .. 21000 Hz **
- Signal to Noise Ratio 92 dB, THD (-3 dBFS) < 0.1 %
- Stereo crosstalk -66 dB

* Hardware revision 2 only

** depends on used codec, best results @48kHz PCM

Serial Interfaces

- RS-232 DSub 9 pin male, 300..115200 Baud
- RS-485 screw terminal block, 300..115200 Baud

Control Interfaces

- web server for control and configuration
- several network API interfaces and serial, depending on loaded firmware

Network Interface

- 10/100Mbps auto-sensing
- RJ-45 connector with integrated Link /Activity LED
- Protocols: TCP/IP, UDP, RTP, SIP, DHCP, Multicast capable

Misc

- Ten status LEDs,
- reset/factory default button
- Internal temperature sensor

Case

- Aluminum, 745 g
- Dimensions: 216 mm x 38 mm x 125 mm (8.5 x 1.5 x 4.92 inch)
- rack and wall mountable using accessories

MTBF

- Min. 300 000h acc. to MIL217F at 25°C ambient temperature

Environmental

Operating Environment

-0 to +40°C / 32 to 104°F

Storage Conditions

-0 to +70°C / 32 to 158°F

both 0 - 70% relative humidity, non-condensing

Certifications

CE, RoHS, others in examination

Ordering Information

2007.9076 Annunicom 1000 INTL

2007.9082 19" Rack mount shelf

2006.9054 Cable set Audio

2014.0095 VSC Active Adapter

Barix AG

Limmatstrasse 21, 8005 Zürich, Switzerland

Phone: +41 434 33 22 11

www.barix.com



Direct Link