
DPRO6 digital audio processor



AGC MULTEAND

d - pro 🕻

PRO 6 is a digital multiband audio processor suited for loudness controlling and peak limiting in FM broadcasting, DAB / HD-Radio, DTV, webcasting and post production applications.

The processing audio chain is composed by a dual band AGC, followed by a six bands limiter.

The final clipper is oversampled and is optimized for digital clipping artifacts reduction, allowing for a clear and natural sound.

All audio processing is realized through DSPs, allowing a stable operation over time and the possibility to implement new functions through software updates.

he D-TV version is equipped with SDI audio embedderdeembedder with automatic bypass in case of failure.

This version can process the audio stream already embedded into the SDI signal, or can be used as an audio embedder to superimpose the audio coming from a mixing console into the SDI signal.

An adjustable delay line will help in lipsyncing the embedded audio to the incoming video.

Technical features:

Analog audio input Sampling frequency 48KHz/24bits Input level +12/-12dBu XLR connectors, electronically balanced

Digital audio input

accepts AES/EBU and SPDIF sample rates from 32 to 96KHz, XLR connector with balanced transformer.

Analog audio output

Output level +12/-12dBu XLR connectors, electronically balanced

Headphones output

1/4" front panel jack Output: 100mW RMS over 50 ohm

Latency Audio processor 8mS

SDI Interface (DTV version)

1 SDI BNC 75 ohm input 3 SDI BNC outputs, one with auto bypass in case of equipment failure

Remote control

All functions can be managed remotely with an included software.

Interfaces

RS-232 (standard on all models) Ethernet streaming card (optional) Ethernet UDP card (optional)

Power supply 100-240VAC 50/60Hz

Physical 1 x 19" rack unit 44mm x 483mm x 156mm Weight 1Kg

ITEL Elettronica e Telecomunicazioni Via S.Penna 82 - 06132 Perugia (PG) Tel - Fax: +39 075 7829669 Email: info@itel.it Web: www.itel.it

